



VMTRP-15R-24

15" Panel-Mount Touch Screen Monitor

- 5-Wire Resistive Touch Screen
- Steel Panel-Mount Enclosure
- Video Inputs: VGA, HDMI DisplayPort
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- 3-Year Warranty

The VMTRP-15R-24 15" industrial-grade touch screen monitors feature rugged steel panel-mount enclosures. The 5-wire resistive touch screen can be activated by almost any object—gloved finger, stylus, pen, etc. They are ideal for use in manufacturing plants, food processing or any other areas where a rugged, flush-mounted touch screen solution is desired. An extensive list of OEM options enables you to customize the VMTRP-15R-24 monitor to meet your exact needs.

All **TRU-Vu** industrial LCD monitors are specifically designed for use in demanding applications. Every **TRU-Vu** monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

Specifications	
MODEL	VMTRP-15R-24
LCD Panel	15" Color TN LCD Panel (LED Backlights)
Touch Technology	5-Wire Resistive Touch
Touch Interface	USB
Resolution	1024 x 768 (XGA)
Viewable Area	11.97" (W) x 8.98" (H) (304.12 x 228.09 mm)
Pixel Pitch	0.297mm
Display Colors	16.2 M
Aspect Ratio	4:3
Brightness	350 nits
Contrast Ratio	700:1
Response Time	8 msec Trf
Viewing Angle	160° (H) x 150° (W)
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA, HDMI, DisplayPort
Power Requirement	12-24VDC (2.5mm Barrel Plug)
Enclosure	Steel Panel-Mount (Rear Clamp)
Operating Temperature	32° to 122° F (0° to 50° C)
Humidity	8-90%RH
Shock	50 G (20 msec, ½ sine)
Vibration	1.5G RMS 10-200 HZ
Dimensions	15.98" (W) x 12.39" (H) (405.80 x 314.60 mm)
Warranty	3 Years