



### ZBVM-24 Series

#### 24" HD Zero-Bezel LCD Monitor

- Zero-Bezel, Seamless, All Glass Front Face
- Sleek Design, Easy to Clean
- Full HD Resolution: 1920 x 1080 (1080p/60)
- Widescreen 16:9 Format
- Dual Built-in Speakers (Rear)
- LED Backlights
- Lockable On-Screen Display (OSD) Controls
- Can Be Customized To Meet Your Needs
- 3 Year Warranty

The ZBVM-24 Series monitors offer the latest look in LCD monitor technology. The Zero-Bezel design removes the front frame (or bezel) used on standard monitors and replaces it with a seamless edge-to-edge piece of glass. Coupled with sleek and slim enclosures, the ZBVM-24 Series monitors are an elegant solution for healthcare, kiosks, hospitality, A/V, commercial, digital signage, and other markets.

However, don't be fooled by its stylish good looks. Inside, the ZBVM-24 Series monitors feature the same high-quality components and rugged performance that TRU-Vu Monitors are known for. They are backed by our standard 3-Year Warranty, and will provide brilliant HD-quality images for years to come. They are available for direct 90-240 VAC operation (without an external power adapter), or 12 VDC/90-240 VAC with an external power brick.


All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.

Specifications			
MODEL	ZBVM-24C-120	ZBVM-24C	ZBVM-24R
LCD Panel	24" TFT Color LCD		
Display Resolution	1920 x 1080 (1080p/60 Full HD)		
Display Area	20.92" x 11.77" (531.4 x 289.9 mm)		
Pixel Pitch	0.248 mm		
Display Colors	16.7M		
Aspect Ratio	16:9		
Brightness	300 nits		
Contrast Ratio	3,000:1		
Viewing Angle	178° (H) x 178° (V)		
Response Time	12 ms Trf		
Control	OSD (On-Screen Display) via Pushbuttons		
Video Inputs	VGA, DVI		VGA, HDMI, DisplayPort
Audio	Dual Rear Speakers		
Power Requirement	90-240 VAC	12 VDC (90-240 VAC with Included Power Brick)	
Power Consumption	25W at 12 VDC/2.1A		
Enclosure	ABS, Zero-Bezel Front Face		
Mounting	Included Tabletop Base and 100 x 100 mm Rear VESA Mount Holes		
Operating Temperature	32° to 122° F (0° to 50° C)		
Humidity	5-90% Non-Condensing		
Vibration	1.5G RMS; Random Wave; 10-200 Hz; 30 mins Per Axis (X,Y,Z)		
Shock	50G, Half-sine Wave, 20 msec, (X,Y,Z)		
Dimensions	22.6" (W) x 13.5" (H) x 2.4" (D) (576.14 x 344.34 x 62.1 mm)		
Weight	13 Lbs. (5.98kg)		
Warranty	3 Years		

### ZBVM-24 Series

24" HD Zero-Bezel LCD Monitor

#### Dimensions:



#### Standard Accessories:

- 90-260 VAC Power Brick (except ZBVM-24-120)
- Tabletop Stand
- VGA Cable
- HDMI Cable
- Audio Cable

#### Available Options:

- Protective/Anti-Reflective Glass Screen
- Touch Screen
- Private Label
- Other Customer - Specific Modifications