

SRM-10.4B

Sunlight-Readable Monitor



- True Sunlight-Readable
- 1,000 nits Brightness
- LED Backlight
- High Shock & Vibration Resistance
- Resolution: 800 x 600 (SVGA)
- Anti-Glare Screen
- NTSC/PAL Auto-Recognition
- Wide Temp. Range (-22° to +185°F)
- Lockable OSD Controls
- High Uniformity (90%)
- Low EMI Noise
- 3 Year Warranty

The SRM-10.4B is designed to operate in direct bright sunlight. TRU-Vu utilizes extra-bright LED backlighting to create amazingly bright images without the excess heat of high wattage CCFL backlights. The SRM-10.4B is ideally suited for industrial, commercial, transportation, military and law enforcement applications requiring a Sunlight-Readable Display. Visit www.TRU-VuMonitors.com for more details.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding industrial, commercial, medical and A/V applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability.

Specifications

LCD Panel	10.4" LED Backlight LCD
Resolution	800 x 600 (SVGA)
Display Area	211.2 x 158.4 mm
Pixel Pitch	0.264 (H) x 0.264 (V)
Display Colors	16.2M
Aspect Ratio	4:3
Brightness	1,000 nits
Contrast Ratio	600:1
Viewing Angle	150° (H) x 150° (V)
Response Time	30 ms
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA, BNC Loop-Thru, NTSC/PAL Auto-Recognition (S-Video & DVI also available)
Power Requirement	12 VDC (90-240 VAC with power adapter)
Power Consumption	9.5W
Enclosure	ABS Housing
Mounting	75 x 75 mm VESA
Operating Temperature	-22° to +185° F / (-30° to +85° C)
Dimensions	9.56" (W) x 7.24" (H) x 0.45" (D) / (242.82 (W) x 183.89 (H) x 11.43 (D) mm)
Weight	1.15 lbs. / (0.5 kg)
Other Models Available:	SRMT-10.4B - As above, with Touchscreen (Anti-Glare Screen)
	SRM-10.4A - VGA, S-Video & Composite Video Inputs
Options	Table-Top Stand