



SRM-10.4 Series 10.4" Sunlight-Readable Monitors

- Produces Clear, Sharp Images Even in Direct, Bright Sunlight
- 1,000 nits Brightness
- LED Backlights
- High Shock & Vibration Resistance
- Lockable OSD Controls
- High Uniformity (90%)
- Low EMI Noise
- 3 Year Warranty

Viewing monitor images outdoors can be very difficult, or impossible. The SRM-10.4 Series monitors are specifically designed to produce clear, sharp images, even with bright, direct sunlight on the face of the screen. This is achieved by using state-of-the-art high-bright LED backlights. These produce brilliant white light, without the excess heat of older high-wattage CCFL backlights. The SRM-10.4 Sunlight Readable monitors are used in a wide variety of industrial, military, law enforcement, aviation, marine, and medical applications where viewability in bright sunlight is critical.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding industrial, commercial, medical and A/V applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Visit www.TRU-VuMonitors.com for more details.

Specifications

MODEL	SRM-10.4A	SRM-10.4B
LCD Panel	10.4" LED Backlight LCD	
Resolution	800 x 600 (SVGA)	
Display Area	211.2 x 158.4 mm	
Pixel Pitch	0.264 (H) x 0.264 (V)	
Display Colors	16.2M	
Aspect Ratio	4:3	
Brightness	1,000 nits	
Contrast Ratio	600:1	
Viewing Angle	140° (H) x 120° (V)	
Response Time	30 ms	
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons	
Video Inputs	VGA, S-Video, Composite, NTSC/PAL Auto-Recognition	BNC Loop-Thru, NTSC/PAL Auto-Recognition (S-Video & DVI also available)
Power Requirement	12 VDC (90-240 VAC with included power adapter)	
Power Consumption	9.5W	
Enclosure	Powder-Coated Steel	
Mounting	75 x 75 mm VESA	
Operating Temperature	-31° to +158° F / -35° to +70° C	
Dimensions	10.1" (W) x 7.9" (H) x 1.7" (D) / 256.53 (W) x 200.66 (H) x 43.18 (D) mm	
Weight	3.8 lbs. / 1.7 kg	
Options Available	Protective Glass, Table-Top Stand, Wall Mount Bracket	