



SRMOB-21.5C

Optically-Bonded Sunlight Readable LCD Monitor

- Sunlight Readable Combined with Optical Bonding
- Resolution: 1920 x 1080 (1080p, Full HD)
- 1,000 nits Brightness
- LED Backlights
- Anti-Reflective Coating on Outer Glass
- VGA & DVI Video Inputs
- Lockable OSD Controls
- Can Be Customized To Meet Your Needs
- 3 Year Warranty

The SRMOB-21.5C Sunlight Readable Monitor is designed to operate in direct bright sunlight or in other high ambient light conditions. TRU-Vu utilizes state-of-the-art LED backlighting to create amazingly bright images. The SRMOB-21.5C is unique in that it also features Optical Bonding, where the LCD panel is bonded to the exterior glass. This eliminates the air gap, which in turn eliminates over 98% of reflections. Optical Bonding also makes the entire monitor more rugged. See the Optical Bonding [article](#) on our website for more details.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding industrial, commercial, medical and A/V applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Visit www.TRU-VuMonitors.com for more details.

Specifications

LCD Panel	21.5" LED Backlit LCD, Optically Bonded
Resolution	1920 x 1080 (SVGA)
Display Area	476.6 mm x 268.1 mm
Pixel Pitch	0.248mm
Display Colors	16:7 m
Aspect Ratio	16:9
Brightness	1,000 nits
Contrast Ratio	800:1
Viewing Angle	160° (H) x 170° (V)
Response Time	5 ms
Control	OSD (On-Screen Display) via Pushbuttons
Video Inputs	VGA, DVI
Power Requirement	12 VDC (90-240 VAC with power brick)
Power Consumption	40W
Enclosure	Powder-Coated Steel
Mounting	100 x 100 mm VESA
Operating Temperature	14° to 122° F / (-10 to 50° C)
Dimensions	19.51" (W) x 11.50" (H) x 0.72" (D) / (495.6 (W) x 292.2 (H) x 18.4 (D) mm)
Weight	6.4 lbs. / (2.9 kg)