

Monitor Selector Guide

Model	LCD Panel	Resolution	Video Inputs	Power Requirements	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time
MV-35F*	3.5" Color LCD	960 x 240	2 BNC Composite, NTSC/PAL	12VDC	4:3	250 nits	300:1	120° (H) x 105° (V)	25 msec
MVF-35F*	3.5" Color Flip-Down	960 x 240	2 BNC Composite, NTSC/PAL	12VDC	4:3	250 nits	300:1	120° (H) x 105° (V)	25 msec
VM-5K	5.5" Color Handheld LCD	960 x 234	Composite, NTSC/PAL	12VDC	4:3	500 nits	400:1	90° (H) x 70° (V)	12 msec
MV-56F*	5.6" Color LCD	1440 x 234	2 BNC Composite, NTSC/PAL	10-36VDC	16:9	200 nits	300:1	130° (H) x 110° (V)	25 msec
RM-555G	Triple 5.7" Color HD Rack Mount	800 x RGB x 480	VGA, S-Video, Component (YPbPr), Analog RGB, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	16:9 / 4:3 Switchable	350 nits	400:1	140° (H) x 130° (V)	8 msec
RM-77G	Dual 7" Color HD Rack Mount	800 x RGB x 480	VGA, S-Video, Component (YPbPr), Analog RGB, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	16:9 / 4:3 Switchable	500 nits	400:1	140° (H) x 115° (V)	10 msec
MV-7F	7" Color LCD	960 x 234	2 BNC Composite, NTSC/PAL	12VDC	4:3	300 nits	300:1	140° (H) x 110° (V)	50 msec
MVF-7F	7" Color Flip-Down	1440 x 234	2 Composite, 16:9 Widescreen, NTSC/PAL	12VDC	16:9	350 nits	500:1	150° (H) x 130° (V)	25 msec
MVW-7F*	7" Color LCD Widescreen	1440 x 234	2 BNC Composite, NTSC/PAL	12VDC (Opt 12-32VDC)	16:9	300 nits	300:1	150° (H) x 130° (V)	25 msec
MVQ-7F*	Quad 7" Color LCD; ABS Housing	1440 x 234	4 BNC Composite, NTSC/PAL	12-24VDC	16:9	300 nits	300:1	150° (H) x 130° (V)	25 msec
MVQ-72F*	Quad 7" Color LCD; Metal Housing	1440 x 234	4 BNC Composite, NTSC/PAL	10-36VDC	16:9	300 nits	400:1	120° (H) x 105° (V)	25 msec
MVQT-72F*	Quad 7" Color Touchscreen; Metal Housing	1440 x 234	4 BNC Composite, NTSC/PAL	10-36VDC	16:9	300 nits	400:1	120° (H) x 105° (V)	25 msec

Monitor Selector Guide

Model	LCD Panel	Resolution	Video Inputs	Power Requirements	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time
MVQT-77F*	Quad 7" Color Touchscreen/DVR/SD Card Reader	1440 x 234	4 BNC Composite, NTSC/PAL	10-36VDC	16:9	300 nits	400:1	120° (H) x 105° (V)	25 msec
MVT-71F with QP-401*	7" Color Touchscreen DVR/SD Reader and External QP-401 Quad Processor	1440 x 234	4 BNC Composite, NTSC/PAL	10-36VDC	16:9	300 nits	350:1	120° (H) x 85° (V)	30 msec
MV-8F*	8" Color LCD Kit	800 x 600	2 BNC Composite, NTSC/PAL	12VDC	4:3	300 nits	500:1	140° (H) x 120° (V)	25 msec
VM-8B	8" Color LCD (Monitor Only)	640 x 480 (VGA)	VGA, Composite, NTSC/PAL	12VDC	4:3	300 nits	250:1	130° (H) x 120° (V)	50 msec
VM-8K	8" Color LCD	640 x 480 (VGA)	VGA, Composite, NTSC/PAL	12VDC	4:3	320 nits	250:1	130° (H) x 120° (V)	50 msec
VMT-10V*	10.4" Color Touchscreen	800 x 600 (SVGA)	VGA	12VDC	4:3	400 nits	500:1	140° (H) x 130° (V)	10 msec
SRM-10.4A	10.4" Color Hi-Brite Sunlight Readable	800 x 600 (SVGA)	VGA, S-Video, Composite	12 VDC / 90-240VAC	4:3	1000 nits	500:1	150° (H) x 150° (V)	35 msec
VM-12A	12" TFT Color LCD	800 x 600 (SVGA)	VGA, S-Video, Composite, NTSC/PAL	12 VDC / 90-240VAC	4:3	400 nits	500:1	140° (H) x 110° (V)	35 msec
VM-12B	12" TFT Color LCD	800 x 600 (SVGA)	VGA, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	4:3	400 nits	500:1	140° (H) x 110° (V)	35 msec
VM-12C*	12" TFT Color LCD	800 x 600 (SVGA)	VGA, DVI-D	12 VDC / 90-240VAC	4:3	400 nits	500:1	140° (H) x 110° (V)	35 msec
VM-15A	15" TFT Color LCD	1024 x 768 (XGA)	VGA, S-Video, Composite, NTSC/PAL	12 VDC / 90-240VAC	4:3	350 nits	700:1	140° (H) x 120° (V)	8 msec (gray to gray)
VM-15B	15" TFT Color LCD	1024 x 768 (XGA)	VGA, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	4:3	350 nits	700:1	140° (H) x 120° (V)	8 msec (gray to gray)
VM-15C	15" TFT Color LCD	1024 x 768 (XGA)	VGA, DVI-D	12 VDC / 90-240VAC	4:3	350 nits	700:1	140° (H) x 120° (V)	8 msec (gray to gray)

Monitor Selector Guide

Model	LCD Panel	Resolution	Video Inputs	Power Requirements	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time
VM-17A	17" TFT Color LCD	1280 x 1024 (SXGA)	VGA, S-Video, Composite, NTSC/PAL	12 VDC / 90-240VAC	4:3	300 nits	800:1	160° (H) x 160° (V)	3 msec (gray to gray)
VM-17B	17" TFT Color LCD	1280 x 1024 (SXGA)	VGA, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	4:3	300 nits	800:1	160° (H) x 160° (V)	3 msec (gray to gray)
VM-17C	17" TFT Color LCD	1280 x 1024 (SXGA)	VGA, DVI-D	12 VDC / 90-240VAC	4:3	300 nits	800:1	160° (H) x 160° (V)	3 msec (gray to gray)
VM-17D	17" TFT Color LCD	1280 x 1024 (SXGA)	VGA, HDMI, Composite (BNC Loop-Through), NTSC/PAL	90-240VAC	4:3	420 nits	500:1	178° (H) x 160° (V)	3 msec (gray to gray)
MM-17B*	17" Medical-Grade TFT Color LCD	1280 x 1024 (SXGA)	VGA, Composite, NTSC/PAL	12 VDC / 100-240VAC	4:3	300 nits	500:1	160° (H) x 160° (V)	5 msec (gray to gray)
VM-19A	19" TFT Color LCD	1280 x 1024 (SXGA)	VGA, S-Video, Composite, NTSC/PAL	12 VDC / 90-240VAC	4:3	300 nits	1300:1	178° (H) x 178° (V)	5 msec (gray to gray)
VM-19B	19" TFT Color LCD	1280 x 1024 (SXGA)	VGA, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	4:3	300 nits	1300:1	178° (H) x 178° (V)	5 msec (gray to gray)
VM-19BL	19" TFT Color LCD	1280 x 1024 (SXGA)	VGA, Composite (BNC Loop-Through), NTSC/PAL	12 VDC / 90-240VAC	4:3	300 nits	800:1	160° (H) x 160° (V)	5 msec (gray to gray)
VM-19C	19" TFT Color LCD	1280 x 1024 (SXGA)	VGA, DVI-D	12 VDC / 90-240VAC	4:3	300 nits	1300:1	178° (H) x 178° (V)	5 msec (gray to gray)
VM-19CL	19" TFT Color LCD	1280 x 1024 (SXGA)	VGA, DVI-D	24 VDC	4:3	300 nits	800:1	160° (H) x 160° (V)	5 msec (gray to gray)
VM-20C	20" TFT Color LCD	1680 x 1050 (WSXGA)	VGA, DVI-D	12 VDC / 90-240VAC	16:9	300 nits	1000:1	160° (H) x 160° (V)	5 msec (gray to gray)
VM-20E	20" TFT Color LCD	1600 x 1200 (UXGA)	VGA, Component (YCbCr), S-Video, DVI, Composite (BNC Loop-Through), NTSC/PAL	24 VDC / 90-240VAC	4:3	300 nits	1000:1	178° (H) x 178° (V)	8 msec (gray to gray)

Monitor Selector Guide

Model	LCD Panel	Resolution	Video Inputs	Power Requirements	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time
VM-26D	26" TFT Color LCD	1366 x 768 (WXGA)	VGA, HDMI, Composite (BNC Loop-Through), NTSC/PAL	24 VDC / 90-240VAC	16:9	500 nits	2500:1	178° (H) x 178° (V)	6.5 msec (gray to gray)
VM-32D2	32" TFT Color LCD	1366 x 768 (WXGA)	VGA, HDMI, Composite (BNC Loop-Through), NTSC/PAL	24 VDC / 90-240VAC	16:9	500 nits	1500:1	178° (H) x 178° (V)	6.5 msec (gray to gray)
VM-32D	32" TFT Color LCD	1920 x 1080 (Full HD)	VGA, HDMI, Composite (BNC Loop-Through), NTSC/PAL	24 VDC / 90-240VAC	16:9	500 nits	4000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)
VM-42E	42" TFT Color LCD	1920 x 1080 (Full HD)	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Through), NTSC/PAL	90-240VAC / 50/60 Hz	16:9	500 nits	5000:1	178° (H) x 178° (V)	8 msec (gray to gray)
VM-47E	47" TFT Color LCD	1920 x 1080 (Full HD)	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Through), NTSC/PAL	90-240VAC / 50/60 Hz	16:9	500 nits	4000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)
VM-52E*	52" TFT Color LCD	1920 x 1080 (Full HD)	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Through), NTSC/PAL	90-240VAC / 50/60 Hz	16:9	500 nits	5000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)

Nearly all monitors can be customized/modified to meet your requirements. All models can be private-labelled. Visit www.Tru-VuMonitors.com for more information.

* = OEM Models; Minimum Order Quantities apply.

Model No. Suffixes:

A = VGA, S-Video, Composite, NTSC/PAL Video Inputs

B = VGA, Composite (BNC Loop-Thru), NTSC/PAL Video Inputs

C = VGA, DVI-D Video Inputs

D = VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL Video Inputs

E = VGA, DVI-D, S-Video, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL Video Inputs

F = Composite, NTSC/PAL Video Inputs

G = VGA, S-Video, Component (YPbPr), Composite (BNC Loop-Thru), NTSC/PAL Video Inputs

J = VGA, DVI-I, S-Video, Composite, NTSC/PAL

K = Kit

L = Low-Cost Model

N = VGA, Composite; NTSC/PAL Video Inputs

R = Rack Mount (12"-20") \$50. adder (Distributor cost)

V = VGA Only