

## TRU-VU Standard Monitor Selector Guide

Model	LCD Panel	Resolution	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time	Power Requirement	Video Inputs
<b>MM-17B</b>	17" Medical-Grade TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	500:1	160° (H) x 160° (V)	5 msec (gray to gray)	12 VDC / 100-240VAC / 50/60 Hz	VGA, Composite, NTSC/PAL
<b>RM-77G</b>	Dual 7" Color HD Rack Mount	800 x RGB x 480	16:9 / 4:3 Switchable	500 nit	400:1	140° (H) x 115° (V)	10 msec	12 VDC / 90-240VAC	VGA, S-Video, Component (YPbPr), Analog RGB, Composite (BNC Loop-Thru), NTSC/PAL
<b>RM-555G</b>	Triple 5.7" Color HD Rack Mount	800 x RGB x 480	16:9 / 4:3 Switchable	350 nit	400:1	140° (H) x 130° (V)	8 msec	12 VDC / 90-240VAC	VGA, S-Video, Component (YPbPr), Analog RGB, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-5K</b>	5.5" TFT Color LCD	960 x 234	4:3	500 nit	400:1	90° (H) x 70° (V)	12 msec	12VDC	Composite, NTSC/PAL
<b>VM-8K</b>	8" TFT Color LCD	640 x 480 (VGA)	4:3	320 nit	250:1	130° (H) x 120° (V)	50 msec	12VDC	VGA, Composite, NTSC/PAL
<b>VM-12A</b>	12" TFT Color LCD	800 x 600 (SVGA)	4:3	400 nit	500:1	140° (H) x 110° (V)	35 msec	12 VDC / 90-240VAC	VGA, S-Video, Composite, NTSC/PAL
<b>VM-12B</b>	12" TFT Color LCD	800 x 600 (SVGA)	4:3	400 nit	500:1	140° (H) x 110° (V)	35 msec	12 VDC / 90-240VAC	VGA, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-12C</b>	12" TFT Color LCD	800 x 600 (SVGA)	4:3	400 nit	500:1	140° (H) x 110° (V)	35 msec	12 VDC / 90-240VAC	VGA, DVI-D
<b>VM-15A</b>	15" TFT Color LCD	1024 x 768 (XGA)	4:3	350 nit	700:1	140° (H) x 120° (V)	8 msec (gray to gray)	12 VDC / 90-240VAC	VGA, S-Video, Composite, NTSC/PAL
<b>VM-15B</b>	15" TFT Color LCD	1024 x 768 (XGA)	4:3	350 nit	700:1	140° (H) x 120° (V)	8 msec (gray to gray)	12 VDC / 90-240VAC	VGA, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-15C</b>	15" TFT Color LCD	1024 x 768 (XGA)	4:3	350 nit	700:1	140° (H) x 120° (V)	8 msec (gray to gray)	12 VDC / 90-240VAC	VGA, DVI-D
<b>VM-17A</b>	17" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	800:1	160° (H) x 160° (V)	3 msec (gray to gray)	12 VDC / 90-240VAC	VGA, S-Video, Composite, NTSC/PAL
<b>VM-17B</b>	17" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	800:1	160° (H) x 160° (V)	3 msec (gray to gray)	12 VDC / 90-240VAC	VGA, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-17C</b>	17" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	800:1	160° (H) x 160° (V)	3 msec (gray to gray)	12 VDC / 90-240VAC	VGA, DVI-D

## TRU-VU Standard Monitor Selector Guide

Model	LCD Panel	Resolution	Aspect Ratio	Brightness	Contrast Ratio	Viewing Angle	Response Time	Power Requirement	Video Inputs
<b>VM-17D</b>	17" TFT Color LCD	1280 x 1024 (SXGA)	4:3	420 nit	500:1	178° (H) x 160° (V)	3 msec (gray to gray)	90-240VAC	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-19A</b>	19" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	1300:1	178° (H) x 178° (V)	8 msec (gray to gray)	12 VDC / 90-240VAC	VGA, S-Video, Composite, NTSC/PAL
<b>VM-19B</b>	19" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	1300:1	178° (H) x 178° (V)	8 msec (gray to gray)	12 VDC / 90-240VAC	VGA, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-19C</b>	19" TFT Color LCD	1280 x 1024 (SXGA)	4:3	300 nit	800:1	178° (H) x 178° (V)	5 msec (gray to gray)	12 VDC / 90-240VAC	VGA, DVI-D
<b>VM-20E</b>	20" TFT Color LCD	1600 x 1200 (UXGA)	4:3	300 nit	1000:1	178° (H) x 178° (V)	8 msec (gray to gray)	24 VDC / 90-240VAC	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-26D</b>	26" TFT Color LCD	1366 x 768 (WXGA)	16:9	500 nit	2500:1	178° (H) x 178° (V)	6.5 msec (gray to gray)	24 VDC / 90-240VAC	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-32D2</b>	32" TFT Color LCD	1366 x 768 (WXGA)	16:9	500 nit	1500:1	178° (H) x 178° (V)	6.5 msec (gray to gray)	24 VDC / 90-240VAC	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-32D</b>	32" TFT Color LCD	1920 x 1080 (Full HD)	16:9	500 nit	4000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)	24 VDC / 90-240VAC	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-42E</b>	42" TFT Color LCD	1920 x 1080 (Full HD)	16:9	500 nit	1500:1	178° (H) x 178° (V)	8 msec (gray to gray)	90-240VAC / 50/60 Hz	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-47E</b>	47" TFT Color LCD	1920 x 1080 (Full HD)	16:9	500 nit	4000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)	90-240VAC / 50/60 Hz	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL
<b>VM-52E</b>	52" TFT Color LCD	1920 x 1080 (Full HD)	16:9	500 nit	5000:1	178° (H) x 178° (V)	6.5 msec (gray to gray)	90-240VAC / 50/60 Hz	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL

\* All monitors can be customized/modified to meet your requirements. Visit [www.Tru-VUMonitors.com](http://www.Tru-VUMonitors.com) for more information.