



MM-24 Series

24" Medical-Grade LCD Monitor

- 24" Medical-Grade LCD Display
- UL 60601 Certified
- Full HD Resolution: 1920 x 1080 (1080p/60)
- Video Inputs: VGA, DVI, HDMI, DisplayPort
- Internal Speakers
- Lockable On-Screen Display Controls
- 3 Year Warranty

The MM-24 Series Medical-Grade monitors are certified to the latest UL 60601-1 regulations. They are ideal for hospital OR/ER/ICU, patient monitoring and information, telemedicine, endoscopy, and other medical applications. The MM-24 Series monitors feature full HD resolution, and provide excellent image quality, color fidelity and image contrast, enabling surgeons to make better and faster decisions with maximum accuracy. The robust yet lightweight design and VESA-compliant rear mounting holes enable flexible mounting options for wall mounts, booms and mobile carts. The MM-24 Series monitors are designed to operate 24/7, and are backed by our full 3-year warranty.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance, greater durability, and a longer life. Visit www.TRU-VuMonitors.com for more details.

	Specifications		
MODEL	MM-24C	MM-24R	MM-24R-X
LCD Panel	24" Color LCD; LED Backlights		
Display Resolution	1920 x 1080 (1080p/60 Full HD)		
Viewable Area	20.92" x 11.77" (531.4 x 298.9 mm)		
Pixel Pitch	0.277mm		
Display Colors	16.7 M		
Aspect Ratio	16:9		
Brightness	300 nits		
Contrast Ratio	5,000:1		
Viewing Angle	178° (H) x 178° (V)		
Response Time	25 ms Trf		
Control	OSD (On-Screen Display) via Front Pushbuttons		
Video Inputs	VGA & DVI-D	VGA, HDMI, DisplayPort	
Audio	Dual Rear Speakers		
Power Requirement	90-240 VAC with Green-Dot Power Cord (Internal Medical-Grade Power Supply)		12 VDC / 90-240 VAC with External Medical-Grade Power Supply
Power Consumption	24W		
Enclosure	ABS (White)		
Mounting	Included Tabletop Base or Via 100x100/200x100mm Rear VESA Mount Holes		
Operating Temperature	32° to 122° F (0° to 50° C)		
Humidity	5-90% RH		
Shock	50G, Half-sine Wave, 20ms, X/Y/Z		
Vibration	Acceleration: 1.5 Grms; Random Wave; 10-200Hz; 30 mins Per Axis (X,Y,Z)		
Dimensions	22.67" (W) x 13.54" (H) x 2.71" (D) (575.8 x 344 x 69 mm)		
Weight	10.52 lbs. (4.77 kg)		
Warranty	3 Years		

