



SXUV-49

49" Water-Resistant LCD Monitor/TV

- Wide Viewing Angle: 178° x 178°
- Video Inputs: VGA, HDMI, YPbPr Component, Composite, Coax
- Auto Re-Start After Power Loss
- Internal Speakers
- Waterproof Universal Remote Control
- 2-Year Warranty

The SXUV-49 is a 49" Water-Resistant LCD monitor/TV, designed for use in harsh, challenging environments, including wood, paper or steel mills, manufacturing plants, and other industrial facilities. It offers 1920 x 1080 full HD-resolution, numerous video inputs and 500 nits of brightness. The SXUV-49 features a weather-resistant, maintenance-free IP55 aluminum enclosure, (no need to ever change filters) and a sealed cable entry system.

Specifications

MODEL	SXUV-49
LCD Panel	49" TFT LCD
Display Resolution	1920 x 1080 Full HD
Viewable Area	42.11" (W) x 23.61" (H) (1069.59 x 599.69mm)
Pixel Pitch	.559 x .559mm
Display Colors	1.06 Billion
Aspect Ratio	16:9
Brightness	500 nits
Contrast Ratio	1,300:1
Viewing Angle	178° (H) x 178° (V)
Response Time	8ms (Gray to Gray)
Refresh Rate	60 Hz
Video Input Connectors	VGA, HDMI (3), Composite (RCA), Component (YPbpr), Coax
Audio Input	VGA Stereo (3.5mm), CVBS Stereo (RCA), YPBPR Stereo (RCA)
Speakers	Dual, 10W @ 8 Ω; Waterproof
Power Requirement	90 VAC to 240 VAC, 47 to 63 Hz
Power Consumption	120 W
Enclosure	Rugged IP 55 Aluminum Enclosure
Mounting	400mm x 300mm VESA Hole Pattern
Operating Temperature	-24°F to +122°F (-31°C to +50° C)
Shock	30 Grms, Half Sine Wave, X,Y,Z one time each direction
Vibration	1.0 Grms, Random Wave, Bandwidth 10-300Hz, Duration X,Y,Z one time each direction
Dimensions	44.43" (W) x 25.93" (H) x 4.15" (D) (1128 x 659 x 105 mm)
Weight	55 lbs. (24.95 kg)
Shipping Weight/Dimensions	60 lbs. (27.21 kg) / 48.38" x 29.87" x 7.0"